



## T-CHARGE 12



### Overview

#### T-CHARGE 12

cod. 807567

Multifunction, battery charger and maintainer for 6/12V WET, GEL, AGM, MF, PbCa, EFB batteries.

Choice of 3 charge voltages in Pulse Tronic: 6V, 12V/1A (motos), 12V/4A (autos).

Advanced specific functions for the charge and maintenance of batteries at low temperatures and of AGM batteries.

The activation of the RECOVERY function allows for the recovery of sulphated batteries.

#### Features:

- Automatic charge and maintenance in Pulse Tronic;
  - 3 charge voltages;
  - Led visualization of the charge level;
  - AGM function for the charge and maintenance of AGM batteries;
  - COLD function to charge and maintain batteries at low temperatures;
  - RECOVERY function to recover sulphated batteries;
  - Protections against overloads, shortcircuit and polarity reversal.
- Equipped with cable with clamps and cable with eyelets.



1 PH 230V



CE MARKING



EAC CERTIFICATION

### Technical data

	CODE 807567		EFFECTIVE CHARGING CURRENT 1 / 4 A		DIMENSIONS 17 x 6,5 x 3,5 cm
	SINGLE PHASE MAINS VOLTAGE 230 V		RATED CHARGE CURR. EN60335-2-29 1 / 4 A		WEIGHT 0,6 kg
	MAINS FREQUENCY 50 / 60 Hz		MIN. RATED REFERENCE CAPACITY 2 Ah		EAN CODE 800489798045 4
	CHARGING ABSORBED POWER 55 W		MAX RATED REFERENCE CAPACITY 70 A		PIECES/PALLET 432 pz/pallet
	CHARGING VOLTAGE 6 / 12 V		PROTECTION DEGREE IP65		PIECES/PALLET - B 288 pz/pallet-B